

## ZK1090-3191-0xxx | EtherCAT cable, PUR, AWG 26, drag-chain suitable

M8, plug, straight, male, 4-pin, A-coded – RJ45, plug, straight, male, 8-pin

### Plugs

Electrical data	Head A	Head B
Rated voltage	30 V (according to IEC 61076-2-104)	125 V
Rated current	4 A at 40 °C (according to IEC 61076-2-104)	1 A at 40 °C
Shielding	yes	yes
Insulation resistance	≥ 100 GΩ (according to IEC 60512)	≥ 100 MΩ (according to IEC 60512)
Mechanical data		
Installation size	M8	RJ45
Connector type	plug	plug
Configuration	straight	straight
Contact type	male	male
Number of positions (face)	4-pin	8-pin
Coding	A-coded	-
Recommended torque, nut	0.4 Nm	-
Mating cycles	≥ 100	≥ 750
Way of locking	screw	-
Weight per piece	0.028 kg (0.0617 lb)	-
Body colour	black	black
Body material	TPU, UL94	PC UL 94 V0
Coupling nut material	GD-Zn, Ni	-
Seal	FPM	-
Contact carrier colour	green	-
Contact carrier material	PA 6, UL 94 V0	PC UL 94
Contact plating	Ni, Au gal.	Ni, Au gal.
Contact material	CuZn	CuZn
Environmental data		
Special features	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1	-
RoHS compliant	yes	yes
Ambient temperature (operation)	-30...+70 °C, -22...+158 °F	-40...+60 °C, -40...+140 °F


Protection class	IP 65/67 in screwed condition (according to IEC 60529)	IP 20
Pollution level	3/2 (according to IEC 60664-1)	3/2 (according to IEC 60664-1)
Approvals	-	UL

## Cable


Electrical data	
Rated voltage	30 V (according to IEC 61076-2-101)
Attenuation of shielding	≥ 43 dB
Insulation resistance	≥ 150 MΩ/km
Unbalanced capacitance to ground	3400 pF/km
Mutual capacitance	51 pF/m at 1 kHz
Characteristic impedance (Ethernet)	100 Ω ±15 Ω (100 MHz)
Loop resistance (Ethernet)	250 Ω/km
Unbalanced resistance (Ethernet)	2 %
Dielectric strength wire/wire (Ethernet)	1000 V DC/700 V AC
Dielectric strength wire/shield (Ethernet)	1000 V DC/700 V AC
Signal running time (Ethernet)	5.55 ns/m
Electrical parameters (Ethernet)	based on CAT 5
Test voltage	700 V
Mechanical data	
Cable structure (Ethernet)	star quad
Conductor construction (Ethernet)	19 x 0.1 mm
Cross section (Ethernet)	1 x 4 x 0.14 mm <sup>2</sup> (AWG26)
Min. bending radius, moved	20 x outer cable diameter
Min. bending radius, fixed installation	4 x outer cable diameter
Weight	40 kg/km (26.9 lb/1000 ft)
Outer cable diameter	5.4 mm ± 0.3 mm (0.213" ±0.0118")
Conductor material (Ethernet)	copper, tinned
Shielding	braiding of tinned copper wires
Optical covering factor of shielding (Ethernet)	90 %
Use	drag-chain suitable
Max. acceleration	10 m/s <sup>2</sup>
Max. speed	15 m/s
Max. number of cycles	20 million (5 million with 14 x D, v = 5 m/s and a = 15 m/s <sup>2</sup> , min. 1 million with 9.5 x D, a = 1 m/s <sup>2</sup> , travel distance = 1 m)
Wall thickness of wire insulation (Ethernet)	0.25 mm
Jacket colour	green
Material jacket	PUR (polyurethane)
Wire colour code	yellow, orange, white, blue
Wire insulation material	PP (polypropylene)
Printing on the jacket	"sequential length in meters" Industrial Ethernet Cat5 trailing * E130266 "UL Recognized" UL AWM 20963 80 °C 30V * ZB9032 "month/year" " internal order number"
Printing colour	black
Environmental data	
Operation temperature range, moved	-40...+80 °C, -40...+176 °F
Oil resistance	according to DIN EN 60811-404 (7x24 h/90 °C)
Acid, lye and solvent resistance	depends on medium, concentration, temperature and duration
CFC-free	yes
Halogen-free	yes
Silicone-free	yes
RoHS compliant	yes
Approvals	UL-Style AWM 20963

Attenuation								
Max. insertion loss								
Frequency [MHz]	1	4	10	16	20	31.25	62.5	100
[db/100 m]	3.1	6.5	9.9	12.3	13.8	17.7	25.6	33.0
[db/100 ft]	0.9	2	3	3.7	4.2	5.4	7.8	10.1
Min. near-end crosstalk attenuation								
Frequency [MHz]	1	4	10	16	20	31.25	62.5	100
[db/100 m]	62	53.0	47.0	44.0	42.0	40.0	35.0	32.0
[db/100 ft]	18.9	16.2	14.3	13.4	12.8	12.2	10.7	9.8

### Contact assembly



### Dimensions



A1	41.00 mm
A2	Ø 10.1 mm
B1	44.0 mm

## Notes

- Depending on the cable length (L), the following length tolerances apply:  
0 m...<0.2 m: ± 10 mm | 0.2...4.0 m: + 40 mm | ≥ 4.0 m: + 1 %
- Illustrations similar
- Further cable length on request. The last three digits of the ordering information is the cable length in decimeters, e.g. ZKxxxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK1090-3191-0002	0.20 m
ZK1090-3191-0004	0.40 m
ZK1090-3191-0005	0.50 m
ZK1090-3191-0006	0.60 m
ZK1090-3191-0010	1.00 m
ZK1090-3191-0015	1.50 m
ZK1090-3191-0020	2.00 m
ZK1090-3191-0025	2.50 m
ZK1090-3191-0030	3.00 m
ZK1090-3191-0035	3.50 m
ZK1090-3191-0050	5.00 m
ZK1090-3191-0055	5.50 m
ZK1090-3191-0060	6.00 m
ZK1090-3191-0070	7.00 m
ZK1090-3191-0075	7.50 m
ZK1090-3191-0080	8.00 m
ZK1090-3191-0090	9.00 m
ZK1090-3191-0100	10.00 m
ZK1090-3191-0110	11.00 m
ZK1090-3191-0120	12.00 m
ZK1090-3191-0125	12.50 m
ZK1090-3191-0140	14.00 m
ZK1090-3191-0150	15.00 m
ZK1090-3191-0160	16.00 m
ZK1090-3191-0165	16.50 m
ZK1090-3191-0170	17.00 m
ZK1090-3191-0200	20.00 m
ZK1090-3191-0205	20.50 m
ZK1090-3191-0250	25.00 m
ZK1090-3191-0285	28.50 m
ZK1090-3191-0300	30.00 m
ZK1090-3191-0310	31.00 m
ZK1090-3191-0325	32.50 m
ZK1090-3191-0400	40.00 m
ZK1090-3191-0500	50.00 m

Accessories	
<b>ZB8801-0000</b>	torque wrench for hexagonal plugs, adjustable
<b>ZB8801-0001</b>	torque cable key, M8/wrench size 9, for ZB8801-0000

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.